



ШЕГЕЛИ ПОЦИНКОВАНИ СЪС СЕРТИФИКАТ ЗА ТОВАРОПОНОСИМОСТ



Работно усилие тона	Φ тяло	Φ болт	Ширина а мм	Височина		Овал 2 кг мм	Единично тегло без гайка кг	Единично тегло с гайка кг
	D мм	D мм		D-тип C мм	Ω-тип C мм			
0.33	5	6	9.5	19	22	16	0.02	
0.50	7	8	12	25	29	20	0.06	0.07
0.75	9	10	13.5	27	32	21	0.11	0.13
1	10	11	17	31	36	26	0.15	0.17
1.5	11	12	19	37	43	29	0.21	0.25
2	13.5	16	20	43	47	32	0.37	0.44
3.25	16	19	27	51	60	43	0.65	0.79
4.75	19	22	32	59	71	51	1.06	1.26
6.5	22	25	36	73	84	58	1.56	1.88
8.5	25	28	43	85	95	68	2.32	2.78
9.5	28	32	46	90	108	75	3.28	3.87
12	32	35	51	94	119	83	4.51	5.26
13.5	35	38	57	115	133	92	5.93	6.94
17	38	42	60	127	146	99	7.89	8.79
25	45	50	73	149	178	126	13.4	14.99
35	50	57	83	171	197	138	18.85	20.65
42.5	57	65	95	190	222	160	26.01	29.01
55	65	70	105	203	260	180	37.86	41.05
85	75	83	127	216	329	190		62.00
120	89	95	146	267	381	230		98.10
180	105	108	165		400	275		160
200	120	130	175		500	290		235
250	130	140	200		540	305		285
300	140	150	200		600	305		340
400	170	175	225		650	325		560
500	180	185	250		700	350		285
600	200	205	275		700	375		880
700	210	215	300		700	400		980
800	210	220	300		700	400		1100
900	220	230	320		700	420		1280
1000	240	240	340		700	420		1460
1250	260	270	360		700	450		1990
1500	280	290	360		700	450		2400